Neoti Complete™

INDOOR LED VIDEO DISPLAYS





910 W. LANCASTER ST., BLUFFTON, IN 46714 SALES@NEOTI.COM | SERVICE@NEOTI.COM



Neoti Complete[™] Series SPECIFICATIONS



Neoti Complete is a pre-packaged, partially assembled dvLED solution that comes in HD and 4K options and sizes.

The included easy-to-install mount, integrated control system, and included LED sections take the guesswork out of configuring and installing a direct-view LED video wall.

Typical install time is less than half a day, with easy-to-follow instructions.

- Includes ADA compliant mount and trim.
- Image enhancement technology allows for improved grayscale and color performance – even in lowbrightness environments.
- Digital and analog audio outputs for sending audio to external sound systems.

		HD 108"	HD 130"	HD 173"	HD 217"	4K 217"	
S	Pixel Pitch	1.2mm	1.4mm	2.0mm	2.5mm	1.2mm	
ZTIE	Resolution (H/V)	512x288 px	384x216 px	320x180 px	256x144 px	512x288 px	
PROPERTIES	Brightness			800 nits			
PRO	Refresh Rate			≥ 1920 Hz			
LAY	Contrast			8000:1			
DISPLAY	Color Depth	18 bit	18 bit 16 bit				
Δ	Diode Type	SMD	1010	SMD 1212	SMD 1515		
	Panel Dimensions (W x H x D)	480 x 540 x 54mm / 18.89" x 21.26" x 2.13"					
ING	Installation & Service	Front					
EER	Operating Voltage	AC 100 ~ 240V					
ENGINEERING	Power (W/sqm)	650/150					
Ĕ	Environment Rating	IP5X Indoor					
	Certifications	FCC, ETL					

Specifications are accurate at time of printing. Actual specifications may vary due to customizations or updates. Specifications should be confirmed upon ordering

